

KOE

JDI Group

Kaohsiung Opto-Electronics Inc.

FOR MESSRS : _____

DATE: Apr. 29th, 2021

CUSTOMER'S ACCEPTANCE SPECIFICATIONS

TX18D210VM0BYA

Contents

| No. | ITEM | SHEET No. | PAGE |
|-----|----------------------------|------------------------------|------------|
| 1 | COVER | 7B64PS 2701-TX18D210VM0BYA-4 | 1-1/1 |
| 2 | RECORD OF REVISION | 7B64PS 2702-TX18D210VM0BYA-4 | 2-1/1 |
| 3 | GENERAL DATA | 7B64PS 2703-TX18D210VM0BYA-4 | 3-1/1 |
| 4 | ABSOLUTE MAXIMUM RATINGS | 7B64PS 2704-TX18D210VM0BYA-4 | 4-1/1 |
| 5 | ELECTRICAL CHARACTERISTICS | 7B64PS 2705-TX18D210VM0BYA-4 | 5-1/2~2/2 |
| 6 | OPTICAL CHARACTERISTICS | 7B64PS 2706-TX18D210VM0BYA-4 | 6-1/2~2/2 |
| 7 | BLOCK DIAGRAM | 7B64PS 2707-TX18D210VM0BYA-4 | 7-1/1 |
| 8 | RELIABILITY TESTS | 7B64PS 2708-TX18D210VM0BYA-4 | 8-1/1 |
| 9 | LCD INTERFACE | 7B64PS 2709-TX18D210VM0BYA-4 | 9-1/6~6/6 |
| 10 | OUTLINE DIMENSIONS | 7B64PS 2710-TX18D210VM0BYA-4 | 10-1/2~2/2 |
| 11 | TOUCH PANEL | 7B64PS 2711-TX18D210VM0BYA-4 | 11-1/1 |
| 12 | APPEARANCE STANDARD | 7B64PS 2712-TX18D210VM0BYA-4 | 12-1/4~4/4 |
| 13 | PRECAUTIONS | 7B64PS 2713-TX18D210VM0BYA-4 | 13-1/2~2/2 |
| 14 | DESIGNATION OF LOT MARK | 7B64PS 2714-TX18D210VM0BYA-4 | 14-1/1 |

ACCEPTED BY: _____

PROPOSED BY: Oblack Tsai

| | | | | |
|---------------------------------|-----------|------------------------------|------|-------|
| KAOHSIUNG OPTO-ELECTRONICS INC. | SHEET NO. | 7B64PS 2701-TX18D210VM0BYA-4 | PAGE | 1-1/1 |
|---------------------------------|-----------|------------------------------|------|-------|

2. RECORD OF REVISION

| DATE | SHEET No. | SUMMARY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------|--|---|--|--------|----------|----|-----------------------|--------|-----|-----|--------------------------|------------------------|-----|------------------------|-----------------|-------------------------|-------------------------|------------|--|---|---|-----|--------------------------------|---|-----|----------------------|---|----|---------------|---|----|----|----|--------|--------|----------|---|----|---------------|---|----|---|----|---|----|---|----|---|----|---|-----------------|---------------------------|---|----|------------|---|----|----|
| Sep.24,'20 | 7B64PS 2710 – TX18D210VM0BYA-2 Page 10-1/1 | 10.1 FRONT VIEW Revised : T/P Thickness : 1.7(Touch Panel) > 1.45(Touch Panel) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 7B64PS 2710 – TX18D210VM0BYA-2 Page 10-2/2 | 10.2 RAER VIEW Revised : Modify the border distance between cover glass and LCM : 1.42 > 0.92 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Oct.30,'20 | 7B64PS 2709 – TX18D210VM0BYA-3 Page 9-1/6 | 9.1 INTERFACE PIN CONNECTIONS Revised : | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><th>Pin No.</th><th>Signal</th><th>Function</th></tr><tr><td>1</td><td>GND</td><td>Ground</td></tr><tr><td>2</td><td>SDA</td><td>Serial data input/output</td></tr><tr><td>3</td><td>SCL</td><td>Serial clock input</td></tr><tr><td>4</td><td>NC</td><td>No Connection</td></tr><tr><td>5</td><td>INT</td><td>Inform host to get finger information. Low active</td></tr><tr><td>6</td><td>RST</td><td>Global reset input. Low active</td></tr><tr><td>7</td><td>Vin</td><td>Power Supply for T/P</td></tr><tr><td>8</td><td>NC</td><td rowspan="3">No Connection</td></tr><tr><td>9</td><td>NC</td></tr><tr><td>10</td><td>NC</td></tr></table> <div>↓</div> <table><tr><th>Pin No</th><th>Signal</th><th>Function</th></tr><tr><td>1</td><td>NC</td><td rowspan="6">No Connection</td></tr><tr><td>2</td><td>NC</td></tr><tr><td>3</td><td>NC</td></tr><tr><td>4</td><td>NC</td></tr><tr><td>5</td><td>NC</td></tr><tr><td>6</td><td>NC</td></tr><tr><td>7</td><td>V_{DD}</td><td>Power Supply for T/P (5V)</td></tr><tr><td>8</td><td>D+</td><td rowspan="2">USB Signal</td></tr><tr><td>9</td><td>D-</td></tr><tr><td>10</td><td>GND</td><td>Ground</td></tr></table> | Pin No. | Signal | Function | 1 | GND | Ground | 2 | SDA | Serial data input/output | 3 | SCL | Serial clock input | 4 | NC | No Connection | 5 | INT | Inform host to get finger information. Low active | 6 | RST | Global reset input. Low active | 7 | Vin | Power Supply for T/P | 8 | NC | No Connection | 9 | NC | 10 | NC | Pin No | Signal | Function | 1 | NC | No Connection | 2 | NC | 3 | NC | 4 | NC | 5 | NC | 6 | NC | 7 | V _{DD} | Power Supply for T/P (5V) | 8 | D+ | USB Signal | 9 | D- | 10 |
| Pin No. | Signal | Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | GND | Ground | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | SDA | Serial data input/output | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | SCL | Serial clock input | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | NC | No Connection | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | INT | Inform host to get finger information. Low active | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | RST | Global reset input. Low active | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | Vin | Power Supply for T/P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | NC | No Connection | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pin No | Signal | Function | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | NC | No Connection | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | V _{DD} | Power Supply for T/P (5V) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | D+ | USB Signal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | D- | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | GND | Ground | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Apr.29,'21 | 7B64PS 2704 – TX18D210VM0BYA-4 Page 4-1/1 | 4. ABSOLUTE MAXIMUM RATINGS Revised : | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 7B64PS 2708 – TX18D210VM0BYA-4 Page 8-1/1 | <table><tr><td>Operating Temperature</td><td>Top</td><td>-40</td><td>85</td></tr></table> <div>↓</div> <table><tr><td>Operating Temperature</td><td>Top</td><td>-30</td><td>80</td></tr></table> 8. RELIABILITY TESTS Revised : <table><tr><td>High Temperature</td><td>1) Operating 2) 85℃</td><td rowspan="3">></td><td>1) Operating 2) 80℃</td></tr><tr><td>Low Temperature</td><td>1) Operating 2) -40℃</td><td>1) Operating 2) -30℃</td></tr><tr><td>Heat Cycle</td><td>1) Operating 2) -40℃ ~85℃ 3) 3hrs~1hr~3hrs</td><td>1) Operating 2) -30℃ ~80℃ 3) 3hrs~1hr~3hrs</td></tr></table> | Operating Temperature | Top | -40 | 85 | Operating Temperature | Top | -30 | 80 | High Temperature | 1) Operating 2) 85℃ | > | 1) Operating 2) 80℃ | Low Temperature | 1) Operating 2) -40℃ | 1) Operating 2) -30℃ | Heat Cycle | 1) Operating 2) -40℃ ~85℃ 3) 3hrs~1hr~3hrs | 1) Operating 2) -30℃ ~80℃ 3) 3hrs~1hr~3hrs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature | Top | -40 | 85 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating Temperature | Top | -30 | 80 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| High Temperature | 1) Operating 2) 85℃ | > | 1) Operating 2) 80℃ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Low Temperature | 1) Operating 2) -40℃ | | 1) Operating 2) -30℃ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Heat Cycle | 1) Operating 2) -40℃ ~85℃ 3) 3hrs~1hr~3hrs | | 1) Operating 2) -30℃ ~80℃ 3) 3hrs~1hr~3hrs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

3. GENERAL DATA

3.1 DISPLAY FEATURES

This module is a 7.0" WVGA of 16:9 format LTPS TFT. The pixel format is vertical stripe and sub pixels are arranged as R(red), G(green), B(blue) sequentially. This display is RoHS compliant, COG (chip on glass) technology and LED backlight are applied on this display.

| | |
|-------------------------|---|
| Part Name | TX18D210VM0BYA |
| Module Dimensions | 167.7(W) mm x 109.5(H) mm x 10.7 (D) mm |
| LCD Active Area | 152.4(W) mm x 91.44(H) mm |
| Pixel Pitch | 0.1905(W) mm x 0.1905 (H) mm |
| Resolution | 800 x 3(RGB)(W) x 480(H) Dots |
| Color Pixel Arrangement | R, G, B Vertical stripe |
| LCD Type | Transmissive Color TFT; Normally Black |
| Display Type | Active Matrix |
| Number of Colors | 262k Colors (6-bit RGB) |
| Backlight | Light Emitting Diode(LED) |
| Weight | 290 g |
| Interface | CMOS 40 pins |
| Power Supply Voltage | 3.3V for LCD; 12V for backlight |
| Power Consumption | 0.20W for LCD; 4.68W for backlight |
| Viewing Direction | Super Wide Version (In-Plane Switching) |
| Touch Panel | Projected Capacitive type; Cover Glass on ITO Film, USB I/F |

4. ABSOLUTE MAXIMUM RATINGS

| Item | Symbol | Min. | Max. | Unit | Remarks |
|-------------------------|-----------|------|--------------|------|---------|
| Supply Voltage | V_{DD} | -0.3 | 4.0 | V | - |
| Input Voltage of Logic | V_I | -0.3 | $V_{DD}+0.3$ | V | Note 1 |
| Operating Temperature | Top | -30 | 80 | °C | Note 2 |
| Storage Temperature | Tst | -40 | 90 | °C | Note 2 |
| Backlight Input Voltage | V_{LED} | - | 14 | V | - |

Note 1: The rating is defined for the signal voltages of the interface such as DE, Hsync, Vsync, CLK and RGB data bus.

Note 2: The maximum rating is defined as above based on the chamber temperature, which might be different from ambient temperature after assembling the panel into the application. Moreover, some temperature-related phenomenon as below needed to be noticed:

- Background color, contrast and response time would be different in temperatures other than 25°C.
- Operating under high temperature will shorten LED lifetime.

5. ELECTRICAL CHARACTERISTICS

5.1 LCD CHARACTERISTICS

$T_a = 25\text{ }^{\circ}\text{C}$, $V_{SS} = 0\text{V}$

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit | Remarks |
|------------------------|-------------|-----------------------------------|-------------|------|-------------|------|---------|
| Power Supply Voltage | V_{DD} | - | 3.0 | 3.3 | 3.6 | V | - |
| Input Voltage of Logic | V_I | "H" level | $0.7V_{DD}$ | - | V_{DD} | V | Note 1 |
| | | "L" level | V_{SS} | - | $0.3V_{DD}$ | | |
| Power Supply Current | I_{DD} | $V_{DD}-V_{SS}$ $=3.3\text{V}$ | - | 60 | 120 | mA | Note 2 |
| Frame Frequency | f_{Frame} | - | - | 60 | 65 | Hz | - |
| CLK Frequency | f_{CLK} | - | 29.7 | 33.3 | 34.6 | MHz | - |

Note 1: The rating is defined for the signal voltages of the interface such as DE, Hsync, Vsync, CLK and RGB data bus.

Note 2: An all white check pattern is used when measuring I_{DD} , f_{Frame} is set to 60 Hz. Moreover, 1.0A fuse is applied in the module for I_{DD} . For display activation and protection purpose, power supply is recommended larger than 2.5A to start the display and break fuse once any short circuit occurred.

5.2 BACKLIGHT CHARACTERISTICS

$T_a = 25\text{ }^{\circ}\text{C}$

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit | Remarks |
|---------------------|-----------|------------------------|------|------|------|------|---------|
| LED Input Voltage | V_{LED} | Backlight Unit | 11.0 | 12.0 | 13.0 | V | Note 1 |
| LED Forward Current | I_{LED} | 0V;0%duty | - | 390 | 430 | mA | Note 2 |
| | | 3.3VDC;100%duty | 10 | 20 | 30 | | |
| LED Lifetime | - | $I_{LED}=390\text{mA}$ | - | 50K | - | hrs | Note 3 |

Note 1: As Fig. 5.1 shown, LED current is constant, 390 mA, controlled by the LED driver when applying 12V.

Note 2: Dimming function can be obtained by applying DC voltage or PWM signal from the display interface CN1. The recommended PWM signal is 1K ~ 10K Hz with 3.3V amplitude.

Note 3: The estimated lifetime is specified as the time to reduce 50% brightness by applying 390 mA at 25° C.




Fig 5.1

Note 4: By applying different I_{LED} , the estimated brightness and LED life time curves are shown as Fig 5.2 and Fig 5.3 for various environment use.




Fig 5.2 LED Current v.s. Brightness




Fig 5.3 LED Current v.s. Lifetime

Note 5: The estimated V_{LED} range is defined to obtain $I_{LED}=390\text{mA}$.

6. OPTICAL CHARACTERISTICS

The optical characteristics are measured based on the conditions as below:

- Supplying the signals and voltages defined in the section of electrical characteristics.
- The backlight unit needs to be turned on for 30 minutes.
- The ambient temperature is 25 °C .
- In the dark room less than 100 lx, the equipment has been set for the measurements as shown in Fig 6.1.

$$T_a = 25\text{ }^{\circ}\text{C}, f_{Frame} = 60\text{ Hz}, V_{DD} = 3.3\text{V}$$

| Item | | Symbol | Condition | Min. | Typ. | Max. | Unit | Remarks |
|-----------------------|-------|---------------|--|------|------|------|----------|---------|
| Brightness of White | | - | $I_{LED}= 390mA$ $\phi = 0^{\circ}, \theta = 0^{\circ}$ | 800 | 1000 | - | cd/m^2 | Note 1 |
| Brightness Uniformity | | - | | 70 | - | - | % | Note 2 |
| Contrast Ratio | | CR | | 700 | 1000 | - | - | Note 3 |
| Response Time | | Tr + Tf | $\phi = 0^{\circ}, \theta = 0^{\circ}$ | - | 30 | 40 | ms | Note 4 |
| NTSC Ratio | | - | $\phi = 0^{\circ}, \theta = 0^{\circ}$ | - | 70 | - | % | - |
| Viewing Angle | | θ_x | $\phi = 0^{\circ}, CR \geq 10$ | - | 85 | - | Degree | Note 5 |
| | | $\theta_{x'}$ | $\phi = 180^{\circ}, CR \geq 10$ | - | 85 | - | | |
| | | θ_y | $\phi = 90^{\circ}, CR \geq 10$ | - | 85 | - | | |
| | | $\theta_{y'}$ | $\phi = 270^{\circ}, CR \geq 10$ | - | 85 | - | | |
| Color Chromaticity | Red | X | $\phi = 0^{\circ}, \theta = 0^{\circ}$ | 0.60 | 0.65 | 0.70 | - | Note 6 |
| | | Y | | 0.27 | 0.32 | 0.37 | | |
| | Green | X | | 0.27 | 0.32 | 0.37 | | |
| | | Y | | 0.56 | 0.61 | 0.66 | | |
| | Blue | X | | 0.10 | 0.15 | 0.20 | | |
| | | Y | | 0.01 | 0.06 | 0.11 | | |
| | White | X | | 0.26 | 0.31 | 0.36 | | |
| | | Y | | 0.28 | 0.33 | 0.38 | | |

Note 1: The brightness is measured from the center point of the panel, P5 in Fig. 6.2, for the typical value.

Note 2: The brightness uniformity is calculated by the equation as below:

$$\text{Brightness uniformity} = \frac{\text{Min. Brightness}}{\text{Max. Brightness}} \times 100\%$$

which is based on the brightness values of the 9 points in active area measured by BM-5 as shown in Fig. 6.2.




Fig 6.1




Fig 6.2

Note 3: The Contrast ratio is measured from the center point of the panel, P5, and defined as the following equation:

$$CR = \frac{\text{Brightness of White}}{\text{Brightness of Black}}$$

Note 4: The definition of response time is shown in Fig. 6.3. The rising time is the period from 10% brightness to 90% brightness when the data is from black to white. Oppositely, Falling time is the period from 90% brightness rising to 10% brightness.




Fig 6.3

Note 5: The definition of viewing angle is shown in Fig. 6.4. Angle ϕ is used to represent viewing directions, for instance, $\phi = 270^\circ$ means 6 o'clock, and $\phi = 0^\circ$ means 3 o'clock. Moreover, angle θ is used to represent viewing angles from axis Z toward plane XY.

The display is super wide viewing angle version, so that the best optical performance can be obtained from every viewing direction.





Fig 6.4

Note 6: The color chromaticity is measured from the center point of the panel, P5, as shown in Fig. 6.2.

7. BLOCK DIAGRAM



Note 1: Signals are a DE, Hsync, Vsync, CLK and RGB data bus.

8. RELIABILITY TESTS

| Test Item | Condition | |
|-----------------------------|---|---|
| High Temperature | 1) Operating 2) 80 °C | 500 hrs |
| Low Temperature | 1) Operating 2) -30 °C | 500 hrs |
| High Temperature | 1) Storage 2) 90 °C | 500 hrs |
| Low Temperature | 1) Storage 2) -40 °C | 500 hrs |
| Heat Cycle | 1) Operating 2) -30 °C ~80 °C 3) 3hrs~1hr~3hrs | 500 hrs |
| Thermal Shock | 1) Non-Operating 2) -40 °C ↔ 85 °C 3) 0.5 hr ↔ 0.5 hr | 500 hrs |
| High Temperature & Humidity | 1) Operating 2) 60 °C & 90%RH 3) Without condensation | 500 hrs (Note 3) |
| Vibration | 1) Non-Operating 2) 10~200 Hz 3) 5G 4) X, Y, and Z directions | 1 hr for each direction |
| Mechanical Shock | 1) Non-Operating 2) 10 ms 3) 80G 4) ±X, ±Y and ±Z directions | Once for each direction |
| ESD | 1) Operating 2) Tip: 150 pF, 330 Ω 3) Air discharge for glass: ±12KV 4) Contact discharge for metal frame: ±15KV | 1) Glass: 9 points 2) Metal frame: 8 points (Note4) |

Note 1: Display functionalities are inspected under the conditions defined in the specification after the reliability tests.

Note 2: The display is not guaranteed for use in corrosive gas environments.

Note 3: Under the condition of high temperature & humidity, if the temperature is higher than 60°C, the humidity needs to be reduced as Fig. 8.1 shown.




Fig. 8.1

Note 4: All pins of LCD interface (CN1) have been tested by ±100V contact discharge of ESD under non-operating condition.

9. LCD INTERFACE

9.1 INTERFACE PIN CONNECTIONS

The display interface connector is FA5S040HP1R3000 made by JAE (Thickness: $0.3 \pm 0.05\text{mm}$; Pitch: $0.5 \pm 0.05\text{mm}$) and more details of the connector are shown in the section of outline dimension.

Pin assignment of LCD interface is as below:

| Pin No. | Signal | Function | Pin No. | Signal | Function |
|---------|-----------------|---------------------------------|---------|-----------------|-----------------------------|
| 1 | V _{DD} | Power Supply for Logic | 21 | G4 | Green Data |
| 2 | V _{DD} | | 22 | G3 | Green Data |
| 3 | UD | Vertical Display mode Control | 23 | V _{SS} | GND |
| 4 | LR | Horizontal Display mode Control | 24 | G2 | Green Data |
| 5 | Vsync | Vertical synchronous signal | 25 | G1 | Green Data |
| 6 | DE | Data Enable Signal | 26 | G0 | Green Data (LSB) |
| 7 | V _{SS} | GND | 27 | V _{SS} | GND |
| 8 | CLK | Dot Clock | 28 | R5 | Red Data (MSB) |
| 9 | V _{SS} | GND | 29 | R4 | Red Data |
| 10 | Hsync | Horizontal synchronous signal | 30 | R3 | Red Data |
| 11 | V _{SS} | GND | 31 | V _{SS} | GND |
| 12 | B5 | Blue Data (MSB) | 32 | R2 | Red Data |
| 13 | B4 | Blue Data | 33 | R1 | Red Data |
| 14 | B3 | Blue Data | 34 | R0 | Red Data (LSB) |
| 15 | V _{SS} | GND | 35 | V _{SS} | GND |
| 16 | B2 | Blue Data | 36 | DIM | Brightness dimming (Note 2) |
| 17 | B1 | Blue Data | 37 | NC | No Connection |
| 18 | B0 | Blue Data (LSB) | 38 | | |
| 19 | V _{SS} | GND | 39 | | |
| 20 | G5 | Green Data (MSB) | 40 | | |

Note 1: Please refer to [9.5 SCAN DIRECTION](#) for the setting methods of UD, LR function.

Note 2: Normal brightness: 0V or 100% PWM duty; Brightness control: 0V to 3.3V DC or 0% to 100% PWM duty.

The backlight connector (CN2) is SM02 (8.0)B-BHS-1-TB(LF)(SN), and pin assignment is as below:

| Pin No. | Signal | Signal |
|---------|------------------|--------|
| 1 | V _{LED} | 12VDC |
| 2 | GND | Ground |

The corrective connector (CN3) of Touch Panel is JAE FA5S010HP1R3000 , and pin assignment is as below:

| Pin No. | Signal | Function |
|---------|-----------------|---------------------------|
| 1 | NC | No Connection |
| 2 | NC | |
| 3 | NC | |
| 4 | NC | |
| 5 | NC | |
| 6 | NC | |
| 7 | V _{DD} | Power Supply for T/P (5V) |
| 8 | D+ | USB Signal |
| 9 | D- | |
| 10 | GND | Ground |

9.2 TIMING CHART

A. SYNCHRONOUS MODE




Fig. 9.1 Horizontal Timing

Note 1: CLK's falling edge is the time to latch data and count ($thp + thb$), therefore, data sending and Hsync's falling edge should start when CLK's rise edge




Fig. 9.2 Vertical Timing

Note 2: Vsync's falling edge needs to start with Hsync's falling edge simultaneously to count ($tvp + tvb$).

B. CLOCK AND DATA INPUT TIMING




Fig. 9.3 Setup & Hold Time




Fig. 9.4 Setup & Hold Time

9.3 TIMING TABLE

The timing sets are based on the best optical performance, frame frequency $f_{Frame} = 60\text{Hz}$ to define. If 60 Hz is not the aim to set, less than 65 Hz for Vsync is recommended to apply for better performance by other parameter combination as the definitions in section 5.1.

A. SYNCHRONOUS MODE

| Item | | Symbol | Min. | Typ. | Max. | Unit |
|-------|---------------------------------|--------|------|------|-------|------|
| Hsync | CLK Frequency | fclk | 29.7 | 33.3 | 34.6 | M Hz |
| | Display Data | thd | 800 | | | CLK |
| | Cycle Time | th | 1048 | 1056 | 1100 | |
| | Pulse Width | thp | 10 | 128 | - | |
| | Back Porch | thb | 10 | 10 | - | |
| | Front Porch | thf | 10 | 118 | - | |
| Vsync | Display Line | tvd | 480 | | | H |
| | Cycle Time | tv | 525 | | | |
| | Pulse Width | tvp | 2 | | | |
| | Back Porch | tvb | 8 | | | |
| | Front Porch | tvf | 35 | | | |
| VH | Phase difference of Vsync-Hsync | - | 0 | - | th-62 | CLK |

Note 1: The rise and fall times (tr, tf) of CLK is equal or less than 3ns.

Other signals are equal or less than 10ns.

Note 2: For timing of input signals, they are set using 30% and 70% of V_{DD} as the base reference.


Note 3: VH Max value is th (Horizontal period)-62.

Note 4: thp+thb should be equal or larger than 26.

B. CLOCK AND DATA INPUT TIMING

| | Item | Symbol | Min. | Typ. | Max. | Unit |
|-------|------------|--------|------|------|------|------|
| CLK | High Time | Tcwh | 12 | - | - | ns |
| | Low Time | Tcwl | 12 | - | - | |
| Vsync | Setup Time | Tvsu | 7 | - | - | |
| | Hold Time | Tvhd | 8 | - | - | |
| Hsync | Setup Time | Thsu | 8 | - | - | |
| | Hold Time | Thhd | 8 | - | - | |
| Data | Setup Time | Tdsu | 7 | - | - | |
| | Hold Time | Tdhd | 6 | - | - | |
| DE | Setup Time | Tesu | 8 | - | - | |
| | Hold Time | Tehd | 8 | - | - | |

9.4 POWER SEQUENCE



Note 1: In order to avoid any damages, V_{DD} has to be applied before all other signals. The opposite is true for power off where V_{DD} has to be remained on until all other signals have been switch off. The recommended time period is 1 second.

Note 2: In order to avoid showing uncompleted patterns in transient state. It is recommended that switching the backlight on is delayed for 1 second after the signals have been applied. The opposite is true for power off where the backlight has to be switched off 1 second before the signals are removed.

Note 3: In order to avoid high Inrush current, V_{DD} rising time need to set between 0.5ms and 10ms.

9.5 SCAN DIRECTION

Scan direction is available to be switched as below by setting CN1's UD & LR pin.



UD : L or Open ; LR : L or Open



UD : L or Open ; LR : H



UD : H ; LR : L or Open




UD : H ; LR : H

9.6 DATA INPUT for DISPLAY COLOR


| Input color | | Red Data | | | | | | Green Data | | | | | | Blue Data | | | | | |
|-------------|------------|----------|----|----|-----|----|----|------------|----|----|-----|----|----|-----------|----|----|-----|----|----|
| | | R5 | R4 | R3 | R2 | R1 | R0 | G5 | G4 | G3 | G2 | G1 | G0 | B5 | B4 | B3 | B2 | B1 | B0 |
| | | MSB | | | LSB | | | MSB | | | LSB | | | MSB | | | LSB | | |
| Basic Color | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red(63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green(63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Blue(63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Cyan | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Magenta | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Yellow | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | White | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| Red | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red (1) | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red (2) | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | Red (62) | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red (63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Green | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green (1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green (2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | Green (62) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green (63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| Blue | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Blue (1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| | Blue (2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| | Blue (62) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 |
| | Blue (63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |

10. OUTLINE DIMENSIONS
10.1 FRONT VIEW



General Tolerance: ±0.5mm
Scale : NTS
Unit : mm

10.2 RAER VIEW





General Tolerance:±0.5mm
Scale : NTS
Unit : mm

11. TOUCH PANEL

The type of touch panel used on this display is capacitive touch panel film, and more characteristics are shown as below:

11.1 MECHANICAL CHARACTERISTICS

| Item | Specification | Remarks |
|-------------------------------|-------------------------------------|--|
| Thickness | 1.45 ± 0.3 mm | Chemically Strengthened Glass |
| CG Material | Soda lime | - |
| Surface Hardness | ≥ 7H | - |
| Input Method | Through a special stylus or finger | - |
| FPC Peeling Force | 5N min. |  |
| FPC Bending Resistance | Meet electrical spec. after testing | Bending area Bending degree: 90 Bending radius: R1.0 mm Bending times: 3 times  |
| Touch Function | 10 points | - |
| Connection insert/remove test | Meet electrical spec. after testing | Insert/remove touch panel FPC for 5 cycles |

11.2 ELECTRICAL CHARACTERISTICS

| Item | Symbol | Condition | Value | | | Unit |
|----------------------|--------------------------|-----------------------|----------------------|------|------|------|
| | | | Min. | Typ. | Max. | |
| Power supply voltage | V _{in} | - | 3.5 | 5.0 | 5.5 | V |
| Crystal Clock | Crystal clock | - | - | 12 | - | MHZ |
| V _{IH} | Input high level voltage | V _{DD} =3.3V | V _{DD} -0.8 | - | - | V |
| V _{IL} | Input low level voltage | - | - | - | 0.8 | V |
| V _{OH} | Output high voltage | I=2mA | V _{DD} -0.4 | - | - | V |
| V _{OL} | Output low voltage | I=2mA | - | - | 0.4 | V |

11.3 CONTROLLER CHARACTERISTICS

The Capacitive Touch Panel features as below:

- Controller IC is EETI EXC3132
- Support USB interface.
- Firmware Version is PCAP3132I_3725_v00

12. APPEARANCE STANDARD

The appearance inspection is performed in a room around 500~1000 lx based on the conditions as below:

- The distance between inspector's eyes and display is 30 cm.
- The viewing zone is defined with angle θ shown in Fig. 12.1 The inspection should be performed within 45° when display is shut down. The inspection should be performed within 5° when display is power on.




Fig. 12.1

12.1 THE DEFINITION OF LCD ZONE

LCD panel is divided into 3 areas as shown in Fig.12.2 for appearance specification in next section.

A zone is the LCD active area (dot area).

B zone is the area between A zone and touch panel V.A.

C zone is the inking area of touch panel.

In terms of housing design, B zone is the recommended window area customers' housing should be located in.




Fig. 12.2

12.2 LCD APPEARANCE SPECIFICATION

The specification as below is defined as the amount of unexpected phenomenon or material in different zones of LCD panel. The definitions of length, width and average diameter using in the table are shown in Fig. 12.3 and Fig. 12.4.

| Item | Criteria | | | | Applied zone |
|---|---------------------------------------|------------------------|----------------|---------------|--------------|
| Scratches | Length (mm) | Width (mm) | Maximum number | Minimum space | A,B |
| | Ignored | $W \leq 0.02$ | Ignored | - | |
| | $L \leq 40$ | $0.02 < W \leq 0.04$ | 10 | - | |
| | - | $0.04 < W$ | Not allowed | - | |
| | Round (Dot Shape) | | | | |
| | Average diameter (mm) | Maximum number | Minimum space | | |
| | $D \leq 0.2$ | Ignore | - | | |
| | $D \leq 0.4$ | 10 | - | | |
| Dent | Serious one is not allowed | | | | A,B |
| Wrinkles in polarizer | Serious one is not allowed | | | | A,B |
| Bubbles on polarizer | Average diameter (mm) | | Maximum number | | A,B |
| | $D \leq 0.3$ | | Ignored | | |
| | $0.3 < D \leq 0.5$ | | 10 | | |
| | $0.5 < D \leq 1.0$ | | 5 | | |
| 1) Stains 2) Foreign Materials 3) Dark Spot | Filamentous (Line shape) | | | | A,B |
| | Length (mm) | Width (mm) | Maximum number | | |
| | Ignored | $W \leq 0.02$ | Ignored | | |
| | $L \leq 2.0$ | $W \leq 0.03$ | 10 | | |
| | $L \leq 1.0$ | $W \leq 0.06$ | 10 | | |
| | Round (Dot shape) | | | | A,B |
| | Average diameter (mm) | Maximum number | Minimum Space | | |
| | $D \leq 0.22$ | Ignored | - | | |
| | $0.22 < D \leq 0.33$ | 5 | - | | |
| | $0.33 < D$ | 0 | - | | |
| | In total | Filamentous + Round=10 | | | |
| | Those wiped out easily are acceptable | | | | |
| Dot-Defect (Note 1) | | Type | Maximum number | | A |
| | Bright dot-defect | 1 dot | 0 | | |
| | | 1 dot | 4 | | |
| | | 2 dots | 1(sets) | | |
| | | In total | 4 | | |
| | In total | | 4 | | |




Fig 12.3



Fig 12.4

Note 1: The definitions of dot defect are as below:

- For bright dot-defect, showing black pattern, visible with 5% ND filter is defined.
- For dark dot-defect, showing white pattern, defect size over 1/2 dot area is defined.
- The definition of 1-dot-defect is the defect-dot, which is isolated and no adjacent defect-dot.
- The definition of adjacent dot is shown as Fig. 12.5.
- The Density of dot defect is defined in the area within diameter $\phi = 10\text{mm}$.







Fig. 12.5

12.3 TOUCH PANEL APPEARANCE SPECIFICATION

The specification as below is defined by the amount of unexpected material in different zones of touch panel.

| Item | Criteria | | | Applied zone |
|-------------------|--------------------------|----------------|----------------|--------------|
| Scratches | Width (mm) | Length (mm) | Maximum number | A,B |
| | $0.08 < W$ | $8 < L$ | Not allowed | |
| | $0.05 < W \leq 0.08$ | $2 < L \leq 8$ | 3 pcs max. | |
| | $W \leq 0.05$ | $L \leq 2$ | 8 max. | |
| Foreign Materials | Filamentous (Line shape) | | | A,B |
| | Width (mm) | Length (mm) | Maximum number | |
| | $0.08 < W$ | $8 < L$ | Not allowed | |
| | $0.05 < W \leq 0.08$ | $2 < L \leq 8$ | 3 pcs max. | |
| | $W \leq 0.05$ | $L \leq 2$ | 8 max. | |
| | Round (Dot shape) | | | A,B |
| | Average diameter (mm) | | Maximum number | |
| | $0.5 < D$ | | Not allowed | |
| | $0.3 < D \leq 0.5$ | | 2 pcs max. | |
| | $0.15 < D \leq 0.3$ | | 10 pcs max. | |
| | $D \leq 0.15$ | | Ignored | |

The limitation of glass flaw occurred on touch panel is defined in the table as below.

| Item | Specifications | |
|------------------|--|---|
| Edge flaw |  | $X \leq 0.5 \text{ mm}$ $Y \leq 0.5 \text{ mm}$ $Z \leq 0.5 \text{ mm}$ |
| Corner flaw |  | $X \leq 0.5 \text{ mm}$ $Y \leq 0.5 \text{ mm}$ $Z \leq 0.5 \text{ mm}$ |
| Progressive flaw |  | Not allowed |

13. PRECAUTIONS

13.1 PRECAUTIONS of ESD

- 1) Before handling the display, please ensure your body has been connected to ground to avoid any damages by ESD. Also, do not touch display's interface directly when assembling.
- 2) Please remove the protection film very slowly before turning on the display to avoid generating ESD.

13.2 PRECAUTIONS of HANDLING

- 1) In order to keep the appearance of display in good condition; please do not rub any surfaces of the displays by sharp tools harder than 3H, especially touch panel, metal frame and polarizer.
- 2) Please do not pile the displays in order to avoid any scars leaving on the display. In order to avoid any injuries, please pay more attention for the edges of glasses and metal frame, and wear finger cots to protect yourself and the display before working on it.
- 3) Touching the display area or the terminal pins with bare hand is prohibited. This is because it will stain the display area and cause poor insulation between terminal pins, and might affect display's electrical characteristics furthermore.
- 4) Do not use any harmful chemicals such as acetone, toluene, and isopropyl alcohol to clean display's surfaces.
- 5) Please use soft cloth or absorbent cotton with ethanol to clean the display by gently wiping. Moreover, when wiping the display, please wipe it by horizontal or vertical direction instead of circling to prevent leaving scars on the display's surface, especially polarizer.
- 6) Please wipe any unknown liquids immediately such as saliva, water or dew on the display to avoid color fading or any permanently damages.
- 7) Maximum pressure to the surface of the display must be less than 1.96×10^4 Pa. If the area of adding pressure is less than 1 cm^2 , the maximum pressure must be less than 1.96N.

13.3 PRECAUTIONS of OPERATING

- 1) Please input signals and voltages to the displays according to the values defined in the section of electrical characteristics to obtain the best performance. Any voltages over than absolute maximum rating will cause permanent damages to this display. Also, any timing of the signals out of this specification would cause unexpected performance.
- 2) When the display is operating at significant low temperature, the response time will be slower than it at 25°C . In high temperature, the color will be slightly dark and blue compared to original pattern. However, these are temperature-related phenomenon of LCD and it will not cause permanent damages to the display when used within the operating temperature.
- 3) The use of screen saver or sleep mode is recommended when static images are likely for long periods of time. This is to avoid the possibility of image sticking.
- 4) Spike noise can cause malfunction of the circuit. The recommended limitation of spike noise is no bigger than $\pm 100 \text{ mV}$.

13.4 PRECAUTIONS of STORAGE

If the displays are going to be stored for years, please be aware the following notices.

- 1) Please store the displays in a dark room to avoid any damages from sunlight and other sources of UV light.
- 2) The recommended long-term storage temperature is between 10°C~35°C and 55%~75% humidity to avoid causing bubbles between polarizer and LCD glasses, and polarizer peeling from LCD glasses.
- 3) It would be better to keep the displays in the container, which is shipped from KOE, and do not unpack it.
- 4) Please do not stick any labels on the display surface for a long time, especially on the polarizer.

13.5 PRECAUTIONS of IMAGE STICKING

- 1) Do not display the fixed image or very frequently repeated clips in a long period of time, it may cause image sticking on display. Even a video of several minutes, which is played in a loop, is considered as repetitive.
- 2) Screensaver or power saving mode is recommended to avoid image sticking effectively. Using moving images, scrolling text and alternating a fixed image with a moving image, are the ideal ways to reduce the possibility of image sticking.
- 3) Additionally, it is important to avoid using static bars at image boundaries. Typically, such bars are a result of difference in aspect ratio (e.g., playing 4:3 content on a 16:9 display).

14. DESIGNATION of LOT MARK

- 1) The lot mark is showing in Fig.14.1. First 4 digits are used to represent production lot, T represented made in Taiwan, and the last 6 digits are the serial number.




Fig. 14.1

- 2) The tables as below are showing what the first 4 digits of lot mark are shorted for.

| Year | Lot Mark | Month | Lot Mark | Month | Lot Mark | Week | Lot Mark |
|------|----------|-------|----------|-------|----------|------------|----------|
| 2020 | 0 | Jan. | 01 | Jul. | 07 | 1~7 days | 1 |
| 2021 | 1 | Feb. | 02 | Aug. | 08 | 8~14 days | 2 |
| 2022 | 2 | Mar. | 03 | Sep. | 09 | 15~21 days | 3 |
| 2023 | 3 | Apr. | 04 | Oct. | 10 | 22~28 days | 4 |
| 2024 | 4 | May | 05 | Nov. | 11 | 29~31 days | 5 |
| | | Jun. | 06 | Dec. | 12 | | |

- 3) Except letters I and O, revision number will be shown on lot mark and following letters A to Z.

- 4) The location of the lot mark is on the back of the display shown in Fig. 14.2.

Label example :



Fig. 14.2